

Rain, Snow and Wind Resistant Withstands winds up to 40 mph

Radiant Patio Heaters

For commercial/residential patios and other outdoor venues

GCRDONGLO ELITE





Summer Never Ends with GordonGlo™ Elite Outdoor Infrared Heating!









Exclusive Benefits of Model GGE

- Long-lasting performance Durable construction to withstand extreme rain or snow, even winds up to 40 mph
 Contlouring comfort
- Gentle uniform comfort
 Spreads heat evenly and provides a soft red glow of infrared energy.
- Lower energy costs Saves energy by heating people, floors and objects, not the air around the space
- Expanded outdoor seating capacity More patrons means more revenue!
- Saves valuable floor space Ceiling or wall mounted under awnings, patios, and covered areas
- Quiet operation No running fan to interfere with guest experience
- Environmentally-conscious NOx emission levels as low as 15 parts per million adjusted for 3% O₂ (below nationally recognized levels as defined by the California Energy Commission)

GordonGlo™ Elite's totally enclosed burner sets the standard in outdoor heating safety and performance.



The above model can only be installed at a 58° angle limiting installation flexibility. As shown, flames are not totally enclosed, evident in darker environments. Exposed flame outside heater is not desirable and can be a potential safety issue if heater is mounted too close to combustibles.



Unlike others, our burner design prevents heat rollout during harsh wind conditions, eliminating exposed flames outside heater. Even when mounted at a 60° angle, burner flame is totally enclosed, as shown above.

Features

- Attractive design Complements any outdoor or indoor décor
- High efficiency tinted ceramic glass Protects burner and improves burner performance
- Indoor or outdoor rated Can be exposed to outdoor elements
- **Durable burner box construction** Weather resistant, zinc plated materials with 3 mil black hi-temperature silicone powder coated paint
- Single (with factory supplied jumper wire) or 2-stage operation
- Available in natural gas or LPG propane
- Available Btu/h inputs (High/Low) 35,000/24,000 or 50,000/34,000

- **Potted (water resistant) direct spark ignition module** For harsh environments
- Horizontal or angle mounting up to 60° Mounting from column or side wall with optional brackets or from ceiling
- **Optional shield** Reduces clearances as low as 10" above heater
- CSA Design Certified ANSI Z83.19 & ANSI Z83.26 Standard
- Warranty 3-year limited warranty on the burner assembly and 1-year limited warranty on controls

GURDONGLO



Glass Surface



Wind Resistance



Rain Resistance

GordonGlo™ Elite Options

Accessories



Heat Shield

Overhead clearances reduction for applications with limited overhead space.



Mounting Bracket

For wall mounting or ceiling mounting at varying angles.



Controls

Two-Stage Remote Control

One remote per heater controls multiple heaters. Wireless remote operation included on select models.



Control Switch

Individual or Zone Control using three-position switch or thermostat.



Installation and service must be performed by a licensed contractor. Installation must conform to manufacturer's Installation, Operation and Service manual and local codes. In the absence of local codes, installation must conform with the National Fuel Gas Code. ANSI Z223.1. Safety: operate heater with proper care and observe all safety precautions per the manufacturer's Installation, Operation and Service manual.

Roberts-Gordon LLC 1250 William Street Buffalo, NY 14206 Telephone: +1.716.852.4400 www.robertsgordon.com

© 2024 Roberts-Gordon LLC. All rights reserved. No part of this work covered by the copyrights herein may be reproduced or copied in any form or by any means – graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems – without written permission of Roberts-Gordon LLC.